

## P/N: 11302-0101

### Copyright

© 2022, FLIR Systems, Inc.

All rights reserved worldwide. Names and marks appearing herein are either registered trademarks or trademarks of FLIR Systems and/or its subsidiaries. All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

### Document identity

Publ. No.: 11302-0101

Commit: 85502

Language:

Modified: 2022-06-02

Formatted: 2022-06-02

### Website

<http://www.flir.com>

### Customer support

<http://support.flir.com>

### Disclaimer

Specifications subject to change without further notice. Camera models and accessories subject to regional market considerations. License procedures may apply. Products described herein may be subject to US Export Regulations. Please refer to [exportquestions@flir.com](mailto:exportquestions@flir.com) with any questions.



General description	
<p>The FLIR A68 is a thermal camera in a very small form factor, designed for machine vision applications where temperature accuracy is not top priority, but rather a stable GigE Vision feed. With 640 x 480 IR resolution and 30 Hz frame rate, it is the ultimate choice for machine vision integration.</p> <p>The FLIR A68 is GigE Vision and GenICam compliant, and compatible with the FLIR Spinnaker SDK, the Teledyne Spera SDK, and third party SDKs.</p>	
<p>Key features:</p> <ul style="list-style-type: none"> <li>• Compact</li> <li>• GigE Vision and GenICam compliant</li> <li>• Power over Ethernet (PoE)</li> <li>• 8-bit or 16-bit IR stream at 640 x 480</li> <li>• Fix focus, adjustable with allen key</li> </ul>	
Imaging and optical data	
Infrared resolution	640 × 480 pixels
Thermal sensitivity (NETD)	< 50 mK @ 25°C ambient
Field of view (FOV)	24.2° × 18.4°
Minimum focus distance	2.0 m (6.6 ft)
Focal length	25 mm (0.98 in)
f-number	1.2
Image frequency	30 Hz
Focus	Fixed
Detector data	
Spectral range	8–14 μm (LWIR)
Detector pitch	17 μm
Ethernet	
Interface	Wired
Connector type	RJ-45
Ethernet, purpose	Control, image, and power
Ethernet, type	Gigabit Ethernet
Ethernet, standard	IEEE 802.3
Ethernet, communication	GigE Vision / GenICam
Ethernet, power	Power over Ethernet (PoE)



# FLIR A68 24°

P/N: 11302-0101

© 2022, FLIR Systems, Inc.

#11302-0101; r. 85502;

<b>Ethernet</b>	
Ethernet, protocols	GigE Vision
Pixel format	Mono8 or 16-bit/pixel
<b>Power system</b>	
Power consumption, typical	<ul style="list-style-type: none"><li>• 12 V: 2.8 W</li><li>• 24 V: 2.8 W</li><li>• PoE (48 V): 3.5 W</li></ul>
Power consumption, maximum	<ul style="list-style-type: none"><li>• 12 V: 4.4 W</li><li>• 24 V: 4.4 W</li><li>• PoE (48 V): 4.8 W</li></ul>
<b>Environmental data</b>	
Operating temperature range	-35°C to +60°C (-31°F to +140°F)
Storage temperature range	-40 to 80°C (-40 to 176°F) To avoid possible damage during storage, ensure that the sensor is not exposed to air. Use a lens cap or lens to cover the sensor.
Humidity (operating and storage)	Maximum 80% relative humidity, non-condensating
EMC	See User manual: <a href="https://support.flir.com/resources/4rur">https://support.flir.com/resources/4rur</a>
Shock	See User manual: <a href="https://support.flir.com/resources/4rur">https://support.flir.com/resources/4rur</a>
Vibration	See User manual: <a href="https://support.flir.com/resources/4rur">https://support.flir.com/resources/4rur</a>
Safety	See User manual: <a href="https://support.flir.com/resources/4rur">https://support.flir.com/resources/4rur</a>
Declaration of conformity	See: <a href="https://support.flir.com/resources/DoC">https://support.flir.com/resources/DoC</a>
<b>Physical data</b>	
Weight (without lens)	67 g (2.4 oz)
Size (L x W x H, without lens)	59 x 29 x 36 mm (2.32 x 1.14 x 1.42 in)
Tripod mounting	UNC ¼"-20
Color	Black
<b>Shipping information</b>	
Packaging, type	Cardboard box
Packaging, contents	<ul style="list-style-type: none"><li>• Infrared camera</li></ul>
Packaging, weight	0.23 kg (0.51 lb)
Packaging, size	130 x 140 x 100 mm (5.1 x 5.5 x 3.9 in)
EAN-13	7332558029503
UPC-12	845188026561
Country of origin	Canada